

- Designed and manufactured by Palas
- Specially for kiosk use
- Uses Axiohm mechanisms and controller boards
- High reliability
- Easy to integrate into kiosks or POS systems
- Simple reloading of paper
- Compact size
- Value priced.



Characteristics	Unit	
Printing Speed	mm/s	Upto 250
Printing Width	mm/s	Upto 56
Resolution	dot/mm	8
Number of Dots	dot/mm	384 or 448
Paper Width	mm/s	60
Paper Roll Diameter	mm	60
Paper Thickness	um	60 to 80
Paper Loading		Auto Loading
Operating Voltage	VDC	12 or 24
Head Pulse Life	pulse	1*10^8
Mechanical Reliability	km	100
Operating Temperature	C/F	-10 to 50 / 14 to 122
Cutter		Auto Cutter
Cutter Life	cut	1 million
Character per Line		24-37
Fonts		CP 437, 737, 850, 852, 858, 860, 862, 863, 865, 866, 1252, 1253
Character Size	dot*dot	12*24 or 16*24
Bar Code Printing		Yes
Data Input Buffer	Kbytes	4
User Flash Memory	Kbytes	192
RAM	Kbytes	128
Interface		RS232 and USB
Command Set		Compatible ESC/POS
Control Output Indication		LED (On board), CDKO Management
CDKO		1
Driver		Windows 98/00/XP , OPOS, Linux
Dimensions	mm	132 (w) x 88 (d) x 113 (h)